



- Fresh Air Intake
- Silent
- Auto Restart Function
- Self-diagnosis Function
- Sleep Mode

Jet-Air
Cool, Warm & Collected
Cassette Split

R410A



Proudly distributed by

JASA
Smart Home

Johannesburg (011)708 1148
Pretoria (012)752 8777
East Rand (011)823 2119
Cape Town (021)823 8866

Durban (031)577 0498
Nelspruit (013)752 3258
Port Elizabeth (041)364 0947
Botswana (00267)262 2909



Cassette Split Type Technical Specifications



- Fresh Air Intake
- Self-diagnosis Function
- Auto Restart Function
- Silent
- Sleep Mode

Model	Indoor		JASA-Ca-H12A4/R	JASA-Ca-H18A4/R	JASA-Ca-H24A4/R	JASA-Ca-H36A4/R	JASA-Ca-H36A5/R	JASA-Ca-H48A5/R	JASA-Ca-H60A5/R	
	Outdoor		JASA-H12A4/R	JASA-H18A4/R	JASA-H24A4/R	JASA-H36A4/R	JASA-H36A5/R	JASA-H48A5/R	JASA-H60A5/R	
Power Supply	V~, Hz Ph		220~240, 50, 1	220~240, 50, 1	220~240, 50, 1	220~240, 50, 1	380~415, 50, 3	380~415, 50, 3	380~415, 50, 3	
Capacity	Cooling	Btu/h	12000	18000	24000	36000	36000	48000	60000	
		kW	3.52	5.28	7.03	10.60	10.60	14.07	17.60	
	Heating	Btu/h	13500	19100	26900	39920	39920	52000	63500	
		kW	3.96	5.60	7.88	11.70	11.70	15.24	18.50	
Electric Data	Rated Cooling Power Input	kW	1.16	1.70	2.26	3.77	3.77	4.90	6.26	
	Rated Heating Power Input	kW	1.22	1.64	2.31	3.50	3.50	5.05	5.78	
	Rated Cooling Current	A	5.32	7.80	10.37	17.30	17.30	22.10	28.10	
	Rated Heating Current	A	5.60	7.52	10.60	16.60	16.60	21.60	27.30	
Performance	EER/COP	W/W	3.03/3.25	3.01/3.41	3.11/3.41	2.81/3.34	2.81/3.34	2.87/3.02	2.81/3.20	
Indoor Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	750/650/580	800/730/660	1200/950/800	1500/1200/1050	1500/1200/1050	1800/1440/1260	1800/1440/1260	
		Noise Level(Hi/Mi/Lo)	dB(A)	46/41/39	45/40/32	45/42/36	48/45/39	48/45/39	53/51/47	53/51/47
	Dimension (W×D×H)	Net(Body)	mm	570×570×260	570×570×260	835×835×250	835×835×250	835×835×250	835×835×290	835×835×290
		Packing(Body)	mm	655×655×295	655×655×295	910×910×310	910×910×310	910×910×310	910×910×350	910×910×350
		Net(Panel)	mm	650×650×55	650×650×55	950×950×55	950×950×55	950×950×55	950×950×55	950×950×55
	Weight	Packing(Panel)	mm	710×710×80	710×710×80	1000×1000×100	1000×1000×100	1000×1000×100	1000×1000×100	1000×1000×100
		Net/Gross(Body)	kg	17.0/20.0	19.0/21.0	25.0/29.0	27.0/30.0	27.0/30.0	28.0/32.0	28.0/32.0
	Net/Gross(Panel)	kg	2.2/3.7	2.2/3.7	5.3/7.8	5.3/7.8	5.3/7.8	5.3/7.8	5.3/7.8	
Outdoor Unit	Noise Level	dB(A)	53	55	57	60	60	60	60	
	Dimension (W×D×H)	Net	mm	730×285×545	800×315×545	825×310×655	970×395×805	970×395×805	940×340×1325	940×340×1325
		Packing	mm	845×370×620	920×400×620	945×435×725	1105×495×895	1105×495×895	1070×450×1435	1070×450×1435
Weight	Net/Gross	kg	28/32	42/45	53/56	65/75	65/75	95/105	99/109	
Refrigerant Pipe	Liquid Side	inch	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	3/8"	
	Gas Side	inch	3/8"	1/2"	5/8"	5/8"	5/8"	3/4"	3/4"	
	Max. Length	m	15	20	20	30	30	50	50	
	Max. Height	m	10	15	15	20	20	30	30	

Due to JASA policy of constant improvement, specifications are subject to change without prior notice.

Remarks: Cooling capacities are based on indoor air temp. 27°C DB, 19°C WB and outdoor air temp. 35°C DB, 24°C WB. The above specifications are subject to change without prior notice for product improvement.


E.O.E.

www.jet-air.co.za

Remark: The above designs and specifications are subject to change of product improvement without prior notice.



12~24K



36K



48~60K

